BOUNDARY DESCRIPTION 118.207 Acres

Situated in the State of Ohio, County of Wayne, Township of Paint in the northwest quarter of Section 14 and the southwest quarter of Section 11, T-15N, R-11W.

Being all of the land described in deeds to **David R. and Kelly Troyer** recorded in official record volume 304, page 27, official record volume 886, page 459 and official record volume 940, page 3673 of the Wayne County records.

Described as follows:

Beginning at a stone monument found marking the southwest corner of the northwest quarter of section 14 – witnessed by a capped reference pin set S 86° 18' 12" E 1.34 feet.

Thence with the following SIXTEEN courses:

- 1) N 03° 34' 53" E 1841.34 feet, along the west line of the quarter section, to the southwest corner of Glenn E. and Celesta A. Hiner, Trustees as described in official record volume 646, page 140 witnessed by a one inch diameter crimped steel pipe found S 86° 59' 50" E 0.71 feet.
- 2) S 86° 59' 50" E 680.11 feet, along the south line of Hiner, to a stone monument found at the southeast corner thereof.
- 3) N 03° 34' 11" E 330.44 feet, along the east line of Hiner, to a capped pin found at the southwest corner of Robert S. and Christa M. Hershberger as described in official record volume 272, page 421.
- 4) S 86° 45' 00" E 180.00 feet, along the south line of Hershberger, to a capped pin found.
- 5) N 03° 34' 11" E 445.48 feet, along the east line of Hershberger, to a 5/8 inch diameter steel pin found.
- 6) N 86° 45' 00" W 83.30 feet, along a northerly line of Hershberger, to a capped pin found.
- 7) N 01° 29' 01" W 111.56 feet, along an easterly line of Hershberger and into the southwest quarter of Section 11 at a distance of 40.14 feet, to a point in Harrison Road (County Road 2) on the southerly line of Milan A. and Clara J. Weaver as described in deed volume 673, page 652 witnessed by a capped reference pin found S 01° 29' 01" E 30.00 feet.
- 8) N 71° 39' 45" E 41.79 feet, along the southerly line of Weaver and in Harrison Road, to a point witnessed by a 5/8 inch diameter steel reference pin found S 01° 29' 01" E 30.00 feet.
- 9) S 01° 29' 01" E 86.85 feet, along a westerly line of Weaver, to a 5/8 inch diameter steel pin found on the south line of the quarter section.

- 10) S 86° 45' 00" E 1159.30 feet, along the south line of the quarter section, to a capped pin found at the northwest corner of Milan A. and Clara J. Weaver as described in official record volume 229, page 448.
- 11) S 03° 38' 42" W 712.80 feet, into the northwest quarter of Section 14 and along the west line of Weaver, to a capped pin set.
- 12) S 86° 45' 00" E 734.25 feet, along the south line of Weaver, to a point on the east line of the quarter section and in Arney Road (Township Road 375) witnessed by a capped reference pin set N 86° 45' 00" W 18.79 feet.
- 13) S 03° 38' 42" W 1281.33 feet, along the east line of the quarter section and for a time in Arney Road, to a capped pin set at the northeast corner of David and Sharon Yoder as described in official record volume 849, page 1544.
- N 87° 06' 16" W 1353.00 feet, along the north line of Yoder, to a capped pin set.
- 15) S 03° 23' 47" W 668.25 feet, along the west line of Yoder, to a capped pin set on the south line of the quarter section.
- 16) S 86° 18' 12" W 1353.77 feet, along the south line of the quarter section, to the Point of Beginning.

This parcel contains 118.207 acres; of which 0.073 acres lie in the southwest quarter of Section 11 and 118.134 acres lie in the northwest quarter of Section 14.

Prior Instrument: official record volume 304, page 27, official record volume 886, page 459 and official record volume 940, page 3673.

Permanent Parcel #: all of 3900182.000, 39-00182.003

This description was prepared by Edward A. Gasbarre, P.S. 7036, from information contained in a survey made under his direction, in May of 2022, on behalf of R.W. Gasbarre & Associates, Inc. A copy of that survey is on file at the Wayne County map office. See survey volume XX, page 216

All bearings are related and common with record survey QQ-679.

All capped pins, both set and found, are 5/8 inch diameter solid steel rods with identification caps marked "GASBARRE WOOSTER, OHIO" unless otherwise noted.

Edward A. Gasbarre, P.S. 7036

H:\ADAT4\AJOBS\2K21\jan\23\TroyeF4\$807\AE

MINIMUM ONAL S-