

BOUNDARY DESCRIPTION
4.000 Acres

Situated in the State of Ohio, County of Wayne, **Township of East Union** in the **northwest quarter of Section 32, T-16N, R-12W.**

Being part of the land described in a deed to **Eli D. Miller, Trustee of the Eli D. Miller and Jemima D. Miller Revocable Trust dated June 27, 2023** recorded in official record volume 960, page 3481 of the Wayne County records.

Described as follows:

Commencing at a capped pin found marking the northwest corner of the northwest quarter of Section 32.

Thence S 88° 59' 27" E 262.99 feet, along the north line of the quarter section, to a railroad spike found in Cutter Road (Township Road 205) at the northwest corner of Danny and Freida Miller as described in official record volume 925, Page 198.

Thence Southwesterly, in Cutter Road, along the west line of Miller and with the arc of a curve concave to the west, a distance of 123.76 feet to a railroad spike found at a point of tangency.

The aforementioned curve has the following properties;

Central Angle = 03° 42' 42"

Chord Distance = 123.74 feet

Radius = 1910.43 feet

Chord Bearing = S 00° 47' 42" W

Thence S 02° 39' 03" W 547.30 feet, in Cutter Road, along the west line of Miller and the extension thereof, to a railroad spike found at a point of curvature on a westerly line of Jonathan A. and Lena S. Yoder as described in official record volume 897, page 3152.

Thence Southwesterly, in Cutter Road, along the westerly line of Yoder and with the arc of a curve to the right, a distance of 241.67 feet to a railroad spike found at a point of tangency.

The aforementioned curve has the following properties;

Central Angle = 09° 40' 00"

Chord Distance = 241.38 feet

Radius = 1432.39 feet

Chord Bearing = S 07° 27' 03" W

Thence S 12° 19' 03" W 52.36 feet, in Cutter Road and along the westerly line of Yoder, to the southwest corner thereof, the **Point of Beginning** for the parcel herein described – witnessed by a capped reference pin found S 88° 53' 48" E 49.34 feet.

Thence with the following FIVE courses:

- 1) **S 88° 53' 48" E 587.75 feet**, along the south line of Yoder, to a capped pin found at the southeast corner thereof.
- 2) **S 01° 22' 37" W 213.84 feet**, along the west line of a 5.650 acre parcel described in a deed to Eli D. Miller, Trustee recorded in official record volume 960, page 3472, to a capped pin found.
- 3) **S 01° 06' 12" W 69.38 feet**, along the west line of the 5.650 acre parcel, a capped pin set.
- 4) **N 88° 53' 48" W 642.88 feet** to a point in Cutter Road on a westerly line of an 8.319 acre parcel described in a deed to Eli D. Miller, Trustee recorded in official record volume 960, page 3481 – witnessed by a capped reference pin set S 88° 53' 48" E 29.24 feet.
- 5) **N 12° 19' 03" E 288.73 feet**, in Cutter Road and along the westerly line of the 8.319 acre parcel, to the **Point of Beginning**.

This parcel contains 4.000 acres and is subject to the access easement described in official record volume 960, page 3472.

Prior Instrument: official record volume 960, page 3481.

Permanent Parcel #: part of 27-00179.011

This description was prepared by Edward A. Gasbarre, P.S. 7036, from information contained in a survey made under his direction, in March of 2024, on behalf of R.W. Gasbarre & Associates, Inc. A copy of that survey is on file at the Wayne County map office. See survey volume XX, page 92

All bearings are related and common with record survey WW-358.

All capped pins, both set and found, are 5/8 inch diameter solid steel rods with identification caps marked "GASBARRE WOOSTER, OHIO" unless otherwise noted.

 3/22/24

Edward A. Gasbarre, P.S. 7036

H:\ADAT4\AJOB52K24\job011\Miller 4.000 Ac Legal.docx



BOUNDARY DESCRIPTION
4.319 Acres

Situated in the State of Ohio, County of Wayne, **Township of East Union** in the **northwest quarter of Section 32, T-16N, R-12W.**

Being part of the land described in a deed to **Eli D. Miller, Trustee of the Eli D. Miller and Jemima D. Miller Revocable Trust dated June 27, 2023** recorded in official record volume 960, page 3481 of the Wayne County records.

Described as follows:

Commencing at a capped pin found marking the northwest corner of the northwest quarter of Section 32.

Thence S 88° 59' 27" E 262.99 feet, along the north line of the quarter section, to a railroad spike found in Cutter Road (Township Road 205) at the northwest corner of Danny and Freida Miller as described in official record volume 925, Page 198.

Thence Southwesterly, in Cutter Road, along the west line of Miller and with the arc of a curve concave to the west, a distance of 123.76 feet to a railroad spike found at a point of tangency.

The aforementioned curve has the following properties;

Central Angle = 03° 42' 42"

Chord Distance = 123.74 feet

Radius = 1910.43 feet

Chord Bearing = S 00° 47' 42" W

Thence S 02° 39' 03" W 547.30 feet, in Cutter Road, along the west line of Miller and the extension thereof, to a railroad spike found at a point of curvature on a westerly line of Jonathan A. and Lena S. Yoder as described in official record volume 897, page 3152.

Thence Southwesterly, in Cutter Road, along the westerly line of Yoder and with the arc of a curve to the right, a distance of 241.67 feet to a railroad spike found at a point of tangency.

The aforementioned curve has the following properties;

Central Angle = 09° 40' 00"

Chord Distance = 241.38 feet

Radius = 1432.39 feet

Chord Bearing = S 07° 27' 03" W

Thence S 12° 19' 03" W 341.09 feet, in Cutter Road, along the westerly line of Yoder and the extension thereof, the **Point of Beginning** for the parcel herein described – witnessed by a capped reference pin set S 88° 53' 48" E 29.24 feet.

Thence with the following FIVE courses:

- 1) **S 88° 53' 48" E 642.88 feet** to a capped pin set on the west line of a 5.650 acre parcel described in a deed to Eli D. Miller, Trustee recorded in official record volume 960, page 3472.
- 2) **S 01° 06' 12" W 280.62 feet**, along the west line of the 5.650 acre parcel, to a 5/8 inch diameter steel pin found at the southwest corner thereof.
- 3) **N 88° 53' 48" W 696.79 feet**, along the north line of Lot 1 of the Hostetler and Ernest Allotment No.1 as recorded in plat volume 33, page 178, to a point in Cutter Road at the southwest corner of an 8.319 acre parcel described in a deed to Eli D. Miller, Trustee recorded in official record volume 960, page 3481 – witnessed by a capped reference pin found S 88° 53' 48" E 30.48 feet.
- 4) **N 11° 19' 03" E 96.95 feet**, along a westerly line of the 8.319 acre parcel, to a point in Cutter Road – witnessed by a capped reference pin found N 88° 58' 30" W 30.49 feet.
- 5) **N 12° 19' 03" E 188.81 feet**, in Cutter Road and along a westerly line of the 8.319 acre parcel, to the **Point of Beginning**.

This parcel contains 4.319 acres.

Prior Instrument: official record volume 960, page 3481.

Permanent Parcel #: part of 27-00179.011

This description was prepared by Edward A. Gasbarre, P.S. 7036, from information contained in a survey made under his direction, in March 2024, on behalf of R. W. Gasbarre & Associates, Inc. A copy of that survey is on file at the Wayne County map office. See survey volume XX, page 921

All bearings are related and common with record survey WW-358.

All capped pins, both set and found, are 5/8 inch diameter solid steel rods with identification caps marked "GASBARRE WOOSTER, OHIO" unless otherwise noted.

Edward A. Gasbarre 3/22/24

Edward A. Gasbarre, P.S. 7036

H:\ADAT4\AJOB\2K24\job011\Miller 4.319 Ac Legal.docx



Eli D. Miller Closure Report 224011

Lot Closure Report - Lot : 4.000 AC

file- H:\ADAT4\AJOB5\2K24\job011\224011.msj\lc_4.000 AC.txt
 Thursday, February 29, 2024, 11:38:53a.m.

Starting location (North, East) = (3962.217, 7962.449)

(In the table below, the Length of Curves refers to the chord length.
 and the Bearing of Curves refers to the chord bearing.)

Leg	Segment	Bearing	Length	Front	End_Northing	End_Easting
1	Line	S88°53'48"E	587.750	No	3950.900	8550.090
2	Line	S01°22'37"W	213.840	No	3737.122	8544.951
3	Line	S01°06'12"W	69.380	No	3667.755	8543.615
4	Line	N88°53'48"W	642.880	No	3680.134	7900.855
5	Line	N12°19'03"E	288.730	No	3962.217	7962.449

Ending location (North, East) = (3962.217, 7962.449)

Total Distance : 1802.580
 Total Traverse Stations : 6
 Misclosure Distance : < 0.001000
 Error of Closure : 1:INFINITY
 Frontage : 0.000
 Frontage/Perimeter : 0.0 percent
 AREA : 174232.562 sq. ft.
= 3.999829 Acres

Lot Closure Report - Lot : 4.319 Ac

Leg	Segment	Bearing	Length	Front	End_Northing	End_Easting
1	Line	S88°53'48"E	642.880	No	3667.755	8543.605
2	Line	S01°06'12"W	280.620	No	3387.187	8538.202
3	Line	N88°53'48"W	696.790	No	3400.604	7841.541
4	Line	N11°19'03"E	96.950	No	3495.669	7860.567
5	Line	N12°19'03"E	188.810	No	3680.132	7900.846

Ending location (North, East) = (3680.132, 7900.846)

Total Distance : 1906.050
 Total Traverse Stations : 6
 Misclosure Direction : N37°45'22"W (from ending location to starting location)
 Misclosure Distance : 0.002
 Error of Closure : 1:1049551.5
 Frontage : 0.000
 Frontage/Perimeter : 0.0 percent
 AREA : 188128.634 sq. ft. (straight segment added to close
 traverse)

= 4.318839 Acres